


Shell PC 1185

SAE 5W-30 Factory Fill Engine Oil



Shell PC 1185 SAE 5W-30 is a high quality engine oil blended for use in General Motors (GM) passenger vehicle Diesel engines for global factory fill requirements.

Applications

Initial fill of GM diesel passenger car and light truck engines. Product meets GM Global Engine Oil Specification for applications requiring GM dexos 2 (formerly GEOS B) engine oil in SAE 5W-30.

Performance Specifications

GM dexos 2

Oil drain intervals

The oil drain interval as specified by the engine manufacturer should be adhered to.

Health & Safety

Shell PC 1185 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Typical Physical Characteristics

Shell PC 1185	
SAE Grade	5W-30
Kinematic Viscosity @ 100°C cSt (ASTM D 445)	12.4
Dynamic Viscosity @ -30°C mPa-s (ASTM D 5293)	< 6600
NOACK Volatility Loss @ 15°C gm/100 gm (CEC-L-40-A-93)	< 13
Pour Point °C (IP 15)	-39.0

These characteristics are typical of current production. Variations in these characteristics may occur.