

# Shell Power Plus 15W-40

*Shell Power Plus has been formulated to help protect and prolong the life of the engine.*

---

## Applications

- **Gasoline & Diesel engines**  
Suitable for a wide range of gasoline fuelled vehicles. Also suitable for naturally aspirated or turbo-charged indirect injection diesel engines where API CF quality oils are specified.

## Performance Features

- **Formulated with anti wear additives.**  
Helps to protect against engine wear and prolong the life of the engine.
- **Oxidation resistance.**  
Resists oil degradation throughout the recommended oil drain interval.

## Performance Specifications

Shell Power Plus is suitable for use where the following specifications are called for:

API Service Classification SL/CF

## Health & Safety

Shell Power Plus is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

## Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.



## Typical Physical Characteristics

<b>Shell Power Plus</b>	<b>15W-40</b>
<b>SAE Viscosity Grade</b>	15W-40
<b>Kinematic viscosity</b> @ 40°C cSt 100°C cSt (ASTM D 445)	100.6 13.66
<b>Viscosity Index</b> (ASTM D 2270)	136
<b>Density</b> @ 15°C kg/l (ASTM D 287)	0.881
<b>Flash Point</b> (PMCC) °C (ASTM D 93)	191
<b>Pour Point</b> °C (ASTM D 97)	-36

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

